

Sikar Bikaner Highway Limited

Regd. Office : The IL&FS Financial Center, Plot C-22, G Block,
 Bandra Kurla Complex, Mumbai- 400051
Tel : 022-26533333 **Fax :** 022-26523979
CIN : U45203MH2012PLC229612

June 13, 2022

Corrigendum – II

S. N.	Description	As per Existing Documents / NIT	As per Revised
1	RFP Volume – I A 1. Scope of Work 1.1.1 vi.	Providing and laying 8mm micro surfacing course as per IRC-SP-81-2008 comprising of dry fine aggregate conforming to Type-III grading of specification, polymer modified cationic slow setting bitumen emulsion(having minimum 60% binder content 3.6% polymer)ordinary portland cement , chemical additives and water in the following proportion.(i)fine aggregate conforming to type-III grading <u>@ 16 kg per sqm of road surface coverage.</u> (ii) bitumen emulsion @ 13% by weight of fine aggregate.,(iii) cement @1.5% by weight of fine aggregate and additive @ 2% by weight of fine aggregate conforming to 514 section of MORT&H complete for finished item of work in all respects as directed by Engineer-in-Charge, duly removing the existing RPM's on the existing bituminous surface .(Including all the cost and conveyance of bitumen emulsion, ordinary Portland cement , cement additives, aggregates, water. this includes crack sealing with VG30sand grout wherever required before micro surfacing as directed by the engineer-in-charge).	Providing and laying 8mm micro surfacing course as per IRC-SP-81-2008 comprising of dry fine aggregate conforming to Type-III grading of specification, polymer modified cationic slow setting bitumen emulsion(having minimum 60% binder content 3.6% polymer)ordinary portland cement , chemical additives and water in the following proportion.(i)fine aggregate conforming to type-III grading <u>@ 13 kg per sqm of road surface coverage.</u> (ii) bitumen emulsion @ 13% by weight of fine aggregate.,(iii) cement @1.5% by weight of fine aggregate and additive @ 2% by weight of fine aggregate conforming to 514 section of MORT&H complete for finished item of work in all respects as directed by Engineer-in-Charge, duly removing the existing RPM's on the existing bituminous surface .(Including all the cost and conveyance of bitumen emulsion, ordinary Portland cement , cement additives, aggregates, water. this includes crack sealing with VG30sand grout wherever required before micro surfacing as directed by the engineer-in-charge).
2	RFP Volume – II - BoQ Bill of Quantities	Providing and Laying of Micro-Surfacing Type-III, aggregate quantity <u>16 Kg/sqm,</u> cationic polymerized bitumen emulsion 13% by wt. of dry aggregate, cement 1%-2% by wt of dry aggregate, additive as needed complete as per IRC Specification SP81:2008, MoRTH Clause 514 (8 mm Thickness for more longevity of pavement)	Providing and Laying of Micro-Surfacing Type-III, aggregate quantity <u>13 Kg/sqm,</u> cationic polymerized bitumen emulsion 13% by wt. of dry aggregate, cement 1%-2% by wt of dry aggregate, additive as needed complete as per IRC Specification SP81:2008, MoRTH Clause 514 (8 mm Thickness for more longevity of pavement)

Authorized Signatory
Sikar Bikaner Highway Limited